

# Technical Specifications

**NETZSCH**

## DSC 300 *Caliris® Classic*

Temperature range	-170°C to 600°C
Heating/Cooling rate	0.001 K/min to 100 K/min*
Temperature accuracy	± 0.1 K (indium)**
Enthalpy precision	± 0.1% for indium
Enthalpy accuracy	< 1% for adamantan, indium, zinc; < 2% for most materials**
Cooling device options	<ul style="list-style-type: none"><li>■ Compressed air cooling (RT to 600°C)</li><li>■ IC40 (-40°C to 600°C)</li><li>■ IC70 (-70°C to 600°C)</li><li>■ LN<sub>2</sub> cooling, automatically controlled (-170°C to 600°C)</li></ul>
Gas atmospheres	Inert, oxidizing, static and dynamic operation
Gas control	<ul style="list-style-type: none"><li>■ Switches for 3 gases included</li><li>■ MFC for 3 gases, optional</li></ul>
ASC	Up to 20 samples and references, optional

\* Maximum rates depend upon the temperature

\*\* Deviation of measured value from "true value" (literature value)

 Prager  
Elektronik

Traunstraße 21, A-2120 Walkersdorf  
T:+43 2245 6725 F:+43 2245 559633  
[office@prager-elektronik.at](mailto:office@prager-elektronik.at)  
[www.prager-elektronik.at](http://www.prager-elektronik.at)