

# Technical Specifications

# NETZSCH

TG 309 Libra®			
	Classic	Select	Supreme
Temperature range	(10°C) RT to 1025°C	(10°C) RT to 1025°C/1100°C	(10°C) RT to 1100°C
Heating rate	0.001 K/min to 200 K/min	0.001 K/min to 200 K/min	0.001 K/min to 200 K/min
Balance resolution	50 ng	20 ng	10 ng
Cooling time <sup>1</sup>	In nitrogen: ≈ 12 min from 1100°C to 100°C In helium: ≈ 5 min from 1100°C to 100°C, ≈10 min to 25°C		
<i>AutoVac</i>	Automatic evacuation and refilling of purge gas; optionally available if MFC is selected		
Temperature resolution	0.001 K	0.001 K	0.001 K
Temperature accuracy <sup>2</sup>	± 0.3 K (after calibration by c-DTA®, indium)		
Temperature calibration	c-DTA®, also for detection of endo- and exothermal effects; Curie standards		
Temperature stability <sup>3</sup>	Peak-to-peak: 0.03 K RMS: 0.005 K		
Temperature precision <sup>4</sup>	0.15 K		
Vacuum-tightness	1 mbar	<< 10 <sup>-1</sup> mbar	<< 10 <sup>-1</sup> mbar
Integrated 4-fold MFC	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Integrated 3-fold MFC	<input type="checkbox"/>	<input type="checkbox"/>	-
Evolved Gas Analysis	-	<input type="checkbox"/>	<input type="checkbox"/>
192+12-position ASC	-	<input type="checkbox"/>	<input type="checkbox"/>
20-position ASC	<input type="checkbox"/>	-	-
Piercing device	-	<input type="checkbox"/>	<input type="checkbox"/>
Color touch display	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Unlimited warranty <sup>5</sup>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

- 21°C chiller temperature, 200 ml/min He (purge + protective gas); the maximum temperature of the TGA system depends on the He gas flow: at 200 ml/min, T<sub>max</sub> is 1020°C.
- Maximum deviation between measured and literature value (indium)
- Measurement at different isothermal temperatures
- Standard deviation based on 10 measurements
- In connection with maintenance contract

included  
 optional

 Prager  
Elektronik

Traunstraße 21, A-2120 Wolkersdorf  
T: +43 2245 6725 F: +43 2245 559633  
office@prager-elektronik.at  
www.prager-elektronik.at